



SHUTTLE



Shown With Options

UP TO
6
PASSENGERS



MAX SPEED
FORWARD
up to 18 MPH

The Shuttle moves four to six passengers safely and quietly. PURE ELECTRIC power means your passengers will not be subjected to exhaust fumes or noise.

The reliability and low maintenance design of the electric drive system powering the shuttle will keep operating and maintenance costs well below those of an internal combustion vehicle.

With an established design, the Shuttle puts controls right where you expect them to be. A low step-in height and class-leading seating offers your passengers convenience and comfort.



- 1 Optional Suntop Available.
- 2 Long and Short Models Available.
- 3 Optional Rear Facing Seat Increases Passenger Count.






COLUMBIA

BUILT FOR WORK



Dimensions

Step Height:	11 in.
Load Bed Height:	27 in.
Ground Clearance:	4.25 in.



Performance

	Short	Long
Max Speed Forward:	18 MPH	
Turning Radius:	Curb to curb - 255 in.	Curb to curb - 356 in.
Range ¹ :	Up to 45 miles	Up to 40 miles

Weight & Capacity

Vehicle Weight :	1,235 lbs.	1,724 lbs.
Rated Capacity ² :	750 lbs.	1,100 lbs.

Power Train

Motor:	Totally enclosed, NEMA class H temperature rated motor
Horsepower:	15.3 HP @1750 rpm
Batteries:	Six 8 volt, heavy duty, 170 amp hour deep cycle
Charger:	Built-in, micro-processor control, fully sealed, anti-drive away interlock, 110-240 VAC, 50/60 HZ
Controller Type:	Programmable, solid state, reduced speed reverse with diagnostic LED & calibrator interface
Controller Rating:	400 amp
Motor Braking Mode:	Regenerative & pedal proportional braking w/top speed limiting
Directional Control:	Dash-mounted safety directional keyswitch
Drive Unit/Differential:	Direct drive, oil bath, helical gears, 10.35:1 final drive ratio

Body

Passenger Capacity:	Two – Four with optional seating	Four – Six with optional seating
Seating:	Bench style, marine grade vinyl, parchment	
Body:	Front – Rhino-Tuff™ polymer Rear – Composite rear body	
Lighting:	Headlights, taillights, brake lights; reflectors optional	
Accessories:	Dash mounted keyswitch; forward & reverse selector; battery discharge indicator; horn; reverse warning alarm	

Chassis

Frame:	High strength tubular steel frame, electrostatically powder coated
Steering:	Automotive rack and pinion
Brakes:	Auto adjusting, dual mechanical rear drum, parking brake automatically releases
Suspension:	Front: Center mounted independent multi-leaf spring with dual shock absorbers Rear: Independent dual coil springs and shock absorbers
Tires:	5.70" x 8", pneumatic, 6-ply rating, load range C

Features, options, specifications, color availability and model designation are subject to change without notice. Some vehicles are pictured with options that may be available at extra cost or may not be available on some models. Ask your dealer about the availability of options and verify that the vehicle you order includes the equipment you require.

¹ Range will vary depending on temperature, grade, payload and driving style. | ² Rated Capacity Includes personnel, cargo, options and accessories.

All specifications are subject to change without notice.

Columbia Vehicle Group, Inc.

A Nordic Group Company | Business Ventures Since 1947

1115 Commercial Ave. Reedsburg, WI 53959
columbiavehicles.com



COLUMBIA



TOMBERLIN